Walk-behind Floor scrubber

F60









MAIN FUNCTIONS AND SPECIFICATIONS

- Work efficiency up to 3000 m²/h;
- Auxiliary traction system / auxiliary power, easier to push;
- Failurereminder/ automatic shutdown to avoid accidents:
- Automatic water stop / solenoidvalve controls the water flow to ensure that the water will be cut off when the brush stops;
- One-clickstart / ECOenergy saving mode,
 The endurance time can reach 5.5h.
- Automatic up and down brushing;Intelligent operation, no need to replace manually.

F60A	Auxiliary traction system
3000m²/h	175rpm
Productivity	Brush speed
510mm	500W
Scrubbing width	Brush motor
830mm	400W
Squeegee width	Suction motor
60L	5h@ECO Mode
Cleanwater tank	Max working duration
65L	12V*2-103Ah
Dirty water tank	Battery type
169.5Kg	23~25Kg
Net weight	Brush down pressure
_	

60 B Mechanical de

1450x830x1100mm

Product size

HOU B	Mechanical design
2000m²/h	175rpm
Productivity	Brush speed
510mm	500W
Scrubbing width	Brush motor
830mm	400W
Squeegee width	Suction motor
60L	5.5h@ECO Mode
Cleanwater tank	Max working duration
65L	12V*2-103Ah
Dirtywater tank	Battery type
161.5Kg	23~25Kg
Net weight	Brush down pressure

1450x830x1100mm

Product size